



4003 FIBERED ROOF RESATURANT & SEALER

APPLICATION METHODS



Application rate at a minimum of 3 gallons per 100 square feet. Application rates will vary by surface, porosity, and job conditions. Please consult Tropical Roofing Products for total dry film thickness requirements.

AVAILABLE SIZES



#4003 Fibered Roof Resaturant & Sealer is ready to use as it comes from the can. **#4003** is a mixture of penetrating solvents, select asphalt, fortifiers, drying agents, and hardeners that give this superior product exceptional quality. **#4003's** strong solvent base enables it to penetrate the old mat, rejuvenating it with fresh oils to keep it from drying out and cracking. The drying agents in **#4003** cure the asphalt enough to make the roof accessible without giving up the essential ductility of the coating. **#4003** forms a continuous durable waterproof seal that will not crack under the harshest of conditions.





#4003 FIBERED ROOF RESATURANT & SEALER

TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

#4003 Fibered Roof Resaturant & Sealer is ready to use as it comes from the can. #4003 is a mixture of penetrating solvents, select asphalt, fortifiers, drying agents, and hardeners that give this superior product exceptional quality. #4003's strong solvent base enables it to penetrate the old mat, rejuvenating it with fresh oils to keep it from drying out and cracking. The drying agents in #4003 cure the asphalt enough to make the roof accessible without giving up the essential ductility of the coating. #4003 forms a continuous durable waterproof seal that will not crack under the harshest of conditions.

FEATURES + BENEFITS

- Revitalizes Worn Out Asphalt Roofs
- Uses Oxidized Asphalt to Form a Harder, More Durable Seal

PHYSICAL PROPERTIES

Maximum V.O.C.	300 g/L
Consistency	Thick black liquid
WPG (Nominal)	8.8 lbs. per gal

PREPARATION

All surfaces must be clean, dry, smooth, even, and free from all other foreign matter. Raised edges, buckles, and blisters should be cut and flattened. Check flashings, drains, edgings, vents, and valleys and repair as needed.

APPLICATION

Apply to clean dry surface using stiff, bristle brush, roller, or spray equipment. For best results, weather should be at least 65°F, dry and clear, with no threat of rain for 48 hours. Drying time is approximately 48 hours in warm, dry weather.

COVERAGE

Apply at the rate of approximately 3 gallons per 100 square feet depending on job specifications. Stir coating to uniform consistency before using. Avoid heavy mounds of mass accumulation.

CLEANUP

Clean tools with mineral spirits or paint thinner.

Flash Point (TCC)	105° F +
Service Temp	40° - 90° F
Drying Time	Average: 2-5 hrs

PRECAUTIONS

DO NOT ALLOW TO FREEZE. DO NOT THIN. DO NOT HEAT CONTAINER or store at temperatures greater than 120°F. Be sure the lid is tight and the pail is secured when transporting this product. Do not allow pail to tumble as this may loosen the lid and allow leakage or spillage to occur.

SHIPPING INFORMATION

D.O.T. Classification: Roof Coating, Not Regulated NFMC #170080

CONTAINER SIZE	CLASS
5 Gal.	55



KEEP OUT OF REACH OF CHILDREN. Close container after each use. DO NOT TAKE INTERNALLY!
If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY!

To the best of our knowledge, all technical data contained herein is true and accurate as of the date of the issuance and subject to change without prior notice. User must contact TROPICAL ROOFING PRODUCTS (TRP) to verify correctness before specifying or ordering. We guarantee our product to conform to the quality control standards established by TRP. We assume no responsibility for coverage, performance or injuries resulting from use. Liability if any, is limited to replacement of the product. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY TRP EXPRESSED OR IMPLIED, STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.